

## Telecom/19" rack



### Specifications

- ? Fixed/Removable side panels
- ? Load bearing capacity of the mounting channel : 270-330 Kg (per running metre )
- ? Mounting channel : Powder coated/ zinc plating with yellow passivation.
- ? Provision of Fan tray for 2/4 fans of 90 CFM 220 V/ 48V DC
- ? Provision for Cables entry :
  - > Top (Round Holes 34 mm Diameter- 10 nos.)
  - > Bottom (Round Holes 34 mm Diameter- 10 nos. & Oval Perforation of 120 x 100 mm)
- ? Material used : Cold Rolled Carbon (CRC) with Thickness varying from 1.6mm to 2.0 mm
- ? Rack Painting : Durable textured polyester Powder coating (Off white) with choice of colour (subject to availability )
- ? Fixing & Earthing : Earth grounding point/stud at the bottom of the panel.

## Dimensions

S.No	Description	Part code	height	Mounting	Width	depth	Doors
1	4U rack	RI/NT/001	280	Wall	600	400,450,500	Front only
2	6U rack	RI/NT/002	370	Wall	600	400,450,500	Front only
3	9U rack	RI/NT/003	500	Wall	600	400,450,500	Front only
4	12U rack	RI/NT/004	650	Wall	600	400,450,500	Front only
5	15U rack	RI/NT/005	770	Wall	600	400,450,500	Front only
6	22U rack	RI/NT/006	1100	Floor	600	300,450,600	Front/back
7	27U rack	RI/NT/007	1320	Floor	600	300,450,600	Front/back
8	32U rack	RI/NT/008	1550	Floor	600	300,450,600	Front/back
9	36U rack	RI/Tx/001	1800	Floor	600	300,450 ,600	Front/back
10	42U Rack	RI/Tx/002	2000	Floor	600	300,450 ,600	Front/back
11	42U Rack	RI/Tx/003	2000	Floor	600	300,450 ,600	Front/back
12	45U Rack	RI/Tx/004	2150	Floor	600	300,450 ,600	Front/back

## Doors Options

- ? Removable front Door with Lock and See-through toughened glass/ perforated sheet steel
- ? Removable Rear Door with Lock M.S. Plane / perforated sheet steel

## Mounting channels

- ? Standard 19" mounting with 2.0 mm thickness ( 2 pair)

## Equipment tray

- ? Heavy duty front & back mounting equipment tray.

## Power distribution unit

- ? PDU with 12 o/p of 5 Amp rating, vertically mounted on back side

## Ventilation

- ? Side panels , rear door 1/3 louvered from bottom for air circulation

## Lock

Locks with universal keys or individual keys (Optional)

## Castors

- ? 2 nos. Un-braking & 2 nos. braking , diagonally fitted,

## Shipment

- ? Factory assembled under stringent quality control minimizing installation time.

## Packing

? Packed in corrugated box with proper shock preventive for glass & other breakable items & moisture proof packing



Office : Plot no 1, Lane no 9, Kadipur ind. area, Gurgaon-122001, Haryana- 122 001 India  
Works : Plot no 1, Lane no 9, Kadipur ind. area, Gurgaon-122001, Haryana- 122 001 India  
Tele fax : +91-124-2212139  
Tel : +91-124-2212139, 6451566  
Hand phone : +91-9910049045 , 9212137283  
email : [Rajbir@rohaninfotech.com](mailto:Rajbir@rohaninfotech.com) , [info@rohaninfotech.com](mailto:info@rohaninfotech.com)  
web : [www.rohaninfo.com](http://www.rohaninfo.com) , [www.rohaninfotech.com](http://www.rohaninfotech.com) ,